

SPECIFICATIONS

MACHINE TYPE:	Upright exposure system with two vacuum trays providing simultaneous double-sided exposure over a 24" x 30" (61 cm x 76 cm) area.
CONSTRUCTION:	Welded steel body with side access doors and front access panel.
FINISH:	Textured paint on the exterior and all metal surfaces painted, anodized or plated.
LAMPS:	Two lamps, 5kw each; Medium pressure multi spectrum lamps.
VACUUM TRAY:	<p>STANDARD: Two trays, with an effective area of 24" x 30" (61 cm x 76 cm). Lower member of each vacuum tray is constructed of glass with a metal frame and is hinged for cleaning. Upper member of each vacuum tray is a metal frame and holds the polyester film for vacuum contact.</p> <p>OPTIONAL LARGE FORMAT: Extended effective area of 26" x 32" (66 cm x 81 cm).</p>
VACUUM SEAL:	"D" gasket sealing.
VACUUM PUMP:	Two 1/4 hp oil-less rotary vane.
OPERATOR INTERFACE:	Programmable logic control with independent exposure program selection and presets.
MACHINE DIMENSIONS:	53½" (136 cm) wide 72" (183 cm) high 99" (251 cm) deep
WEIGHT:	2400 pounds (1089 kg)